

# SAFETY DATA SHEET

## **ANGUS CHEMICAL COMPANY**

Product name : ZOLDINE™ LH 2001, Rapid Cure Liquid Hardener for PRF Wood Adhesives

nderstand the entire (M)SDS,

Issue Date: 11/02/2017

Print Date: 11/03/2017

ANGUS CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name ZOLDINE™ LH 2001, Rapid Cure Liquid Hardener

for PRF Wood Adhesives

Manufacturer or supplier's details

Company name of supplier ANGUS CHEMICAL COMPANY

Address 1500 E. LAKE COOK ROAD

Buffalo Grove IL 60089-6553

**Customer Information** 

Number

+1-847-808-3711

E-mail address NAR\_CC@ANGUS.COM

**Emergency telephone** 

number

800-424-9300

# Recommended use of the chemical and restrictions on use

Recommended use Resin curing chemical use in wood adhesives

The ANGUS Chemical Company recommends that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact the Customer Information Group (see

Section 1 of this data sheet).

#### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Flammable liquids Category 4

Acute toxicity (Inhalation) Category 4

Liquid Hardener for PRF Wood Adhesives

Skin irritation Category 2

Serious eye damage Category 1

Skin sensitisation Sub-category 1A

# GHS Label elements, including precautionary statements

Hazard pictograms

Signal word Danger

Hazard statements Combustible liquid.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

Harmful if inhaled.

# Precautionary statements

# Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Issue Date: 11/02/2017

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/ eye protection/ face protection.

#### Response:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

# Storage:

Store in a well-ventilated place. Keep cool.

# Disposal:

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a substance.

#### Components

Chemical Name	CAS-No.	Concentration (% w/w)
7a-Ethyldihydro-1H,3H,5H-	7747-35-5	>= 94.0 %
oxazolo(3,4-c)oxazole		
4-Ethyl-4-(hydroxymethyl)oxazolidine	535978-60-0	<= 4.0 %

#### 4. FIRST AID MEASURES

If inhaled Move person to fresh air. If person is not breathing, call an

emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for

Issue Date: 11/02/2017

treatment advice.

In case of skin contact

Take off contaminated clothing. Wash skin with soap and

plenty of water for 15-20 minutes. Call a poison control center

or doctor for treatment advice.

Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of

properly.

Suitable emergency safety shower facility should be available

in work area.

In case of eye contact Wash immediately and continuously with flowing water for at

least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist.

Suitable emergency eye wash facility should be immediately

available.

If swallowed Call a poison control center or doctor immediately for

treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the

poison control center or doctor.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11:

Toxicology Information.

Protection of first-aiders First Aid responders should pay attention to self-protection

and use the recommended protective clothing (chemical

resistant gloves, splash protection).

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Notes to physician Treatment of exposure should be directed at the control of

symptoms and the clinical condition of the patient.

No specific antidote.

Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control

Issue Date: 11/02/2017

center or doctor, or going for treatment.

## 5. FIREFIGHTING MEASURES

Suitable extinguishing media Water fog or fine spray.

Carbon dioxide fire extinguishers. Dry chemical fire extinguishers.

Foam.

Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams

may function, but will be less effective.

Specific hazards during

firefighting

Container may rupture from gas generation in a fire situation.

Hazardous combustion

products

During a fire, smoke may contain the original material in addition to combustion products of varying composition which

may be toxic and/or irritating.

Combustion products may include and are not limited to:

Carbon dioxide. Carbon monoxide. Nitrogen oxides.

Further information Keep people away. Isolate fire and deny unnecessary entry.

Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Burning liquids may be extinguished by dilution with water. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container.

Move container from fire area if this is possible without hazard.

Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has

passed.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves).

Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote

location.

For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Issue Date: 11/02/2017

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Keep upwind of spill.

Ventilate area of leak or spill.

No smoking in area.

Only trained and properly protected personnel must be

involved in clean-up operations.

Evacuate area.

Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Refer to section 7, Handling, for additional precautionary

measures.

**Environmental precautions** 

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up

Contain spilled material if possible.

Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional

information.

## 7. HANDLING AND STORAGE

Advice on safe handling Avoid breathing vapor.

Keep away from heat, sparks and flame.

Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar

operations on or near empty containers.

Wash thoroughly after handling. Use with adequate ventilation.

Keep container closed. Do not get in eyes.

Avoid contact with skin and clothing.

Avoid prolonged or repeated contact with skin.

See Section 8, EXPOSURE CONTROLS AND PERSONAL

PROTECTION.

Conditions for safe storage

Recommend storage in a cool, dry place away from high

temperatures, hot pipes and direct sunlight.

Do not store in: Aluminum. Aluminum alloys.

Copper.
Copper alloys.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures Local exhaust ventilation may be necessary for some

operations.

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or

Issue Date: 11/02/2017

guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be

sufficient for most operations.

#### Personal protective equipment

Respiratory protection Respiratory protection should be worn when there is a

potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an

approved air-purifying respirator.

The following should be effective types of air-purifying

respirators:

Organic vapor cartridge with a particulate pre-filter, type AP2.

Hand protection

Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton. Butyl rubber.

Neoprene. Polyvinyl chloride ("PVC" or "vinyl").

Nitrile/butadiene rubber ("nitrile" or "NBR"). Avoid gloves made of: Polyvinyl alcohol ("PVA"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body

reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

instructions/specifications provided by the glove supplie

Eye protection Use chemical goggles.

Selection of specific items such as face shield, boots, apron,

or full body suit will depend on the task.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Issue Date: 11/02/2017

**Appearance** Liquid.

Color Colorless

Odor Amine.

Odor Threshold No test data available

10 (22 °C) рΗ

> Method: Literature (0.1 M in water)

Melting point/range 1 °C (34 °F)

Method: EC Method A1

Freezing point 1 °C (34 °F)

Method: EC Method A1

Boiling point/boiling range 187 °C (369 °F)

Method: Literature

Flash point 79 °C (174 °F)

Method: Tag Closed Cup ASTM D56

Test Type: closed cup

No test data available Evaporation rate

No data available. Flammability (solid, gas)

Upper explosion limit No test data available

Lower explosion limit No test data available

Vapor Pressure 0.45 mmHg

Method: Literature

25°C (77°F)

Relative Vapor Density (air =

No test data available

Relative density 1.08 (20 °C)

Method: EC Method A3

Water solubility Miscible with water in all proportions

Partition coefficient: n-

octanol/water

log Pow: -0.32

Method: EC Method A6

Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

230 °C Auto-ignition temperature

Method: EC Method A13

Decomposition temperature No test data available

Viscosity

Viscosity, dynamic 5.2 mPa.s (20 °C)

Method: OECD 114

Explosive properties No data available.

Oxidizing properties No data available.

Surface tension 71.4 mN/m, 25 °C

Molecular weight 143.19 g/mol

Method: Literature

NOTE: The physical data presented above are typical values and should not be construed as a specification.

## 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability Stable under recommended storage conditions. See Storage,

Section 7.

Conditions to avoid Exposure to elevated temperatures can cause product to

decompose.

Generation of gas during decomposition can cause pressure

Issue Date: 11/02/2017

in closed systems.

Incompatible materials Reaction with acid can generate flammable formaldehyde gas.

Avoid contact with oxidizing materials.

Avoid contact with:

Strong acids.

Halogenated hydrocarbons. Avoid unintended contact with:

Acidic pH.

Hazardous decomposition

products

Decomposition products depend upon temperature, air supply

and the presence of other materials.

Toxic flammable gases can be released during

decomposition.

Decomposition products can include and are not limited to:

Formaldehyde.

## 11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

# **Acute toxicity**

# **Product:**

 $Product\ name: {\tt ZOLDINE^{TM}}\ LH\ 2001,\ Rapid\ Cure$ 

Liquid Hardener for PRF Wood Adhesives

Acute oral toxicity Remarks: Small amounts swallowed incidentally as a result of

normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Issue Date: 11/02/2017

Low toxicity if swallowed.

LD50 (Rat): > 3,600 mg/kg

Acute inhalation toxicity Remarks: At room temperature, exposure to vapor is minimal

due to low volatility.

Vapor from heated material or mist may cause respiratory

irritation.

Based on the available data, narcotic effects were not

observed.

LC50 (Rat): 3.1 mg/l Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity Remarks: Prolonged skin contact is unlikely to result in

absorption of harmful amounts.

LD50

(Rat, male and female): > 2,000 mg/kg

# **Components:**

## 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Acute oral toxicity LD50 (Rat, male): > 3,674 mg/kg

Other (Rat, female): 5,249 mg/kg

Acute inhalation toxicity Remarks: At room temperature, exposure to vapor is minimal

due to low volatility.

Vapor from heated material or mist may cause respiratory

irritation.

Based on the available data, narcotic effects were not

observed.

LC50 (Rat): 3.1 mg/l Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity LD50 (Rat, male and female): > 2,000 mg/kg

# 4-Ethyl-4-(hydroxymethyl)oxazolidine

Acute oral toxicity Remarks: Single dose oral LD50 has not been determined.

Acute inhalation toxicity Remarks: The LC50 has not been determined.

Acute dermal toxicity Remarks: The dermal LD50 has not been determined.

Acute oral toxicity LD50 (Rat, male): > 3,674 mg/kg

Other (Rat, female): 5,249 mg/kg

Acute inhalation toxicity Remarks: At room temperature, exposure to vapor is minimal

due to low volatility.

Vapor from heated material or mist may cause respiratory

Issue Date: 11/02/2017

irritation.

Based on the available data, narcotic effects were not

observed.

LC50 (Rat): 3.1 mg/l Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity LD50 (Rat, male and female): > 2,000 mg/kg

#### Skin corrosion/irritation

#### **Product:**

Result: Skin irritation

Remarks: Repeated contact may cause severe skin irritation with local redness and discomfort.

Prolonged contact may cause severe skin irritation with local redness and discomfort.

Remarks: Not classified as corrosive to the skin according to DOT guidelines.

## **Components:**

## 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Result: Skin irritation

Remarks: Brief contact may cause slight skin irritation with local redness.

Repeated contact may cause severe skin irritation with local redness and discomfort. Prolonged contact may cause severe skin irritation with local redness and discomfort.

Remarks: Not classified as corrosive to the skin according to DOT guidelines.

Result: Skin irritation

Remarks: Brief contact may cause slight skin irritation with local redness.

Repeated contact may cause severe skin irritation with local redness and discomfort. Prolonged contact may cause severe skin irritation with local redness and discomfort.

Remarks: Not classified as corrosive to the skin according to DOT guidelines.

## Serious eye damage/eye irritation

## Product:

Result: Corrosive

Remarks: May cause severe irritation with corneal injury which may result in permanent

impairment of vision, even blindness. Chemical burns may occur.

Mist may cause eye irritation.

#### Components:

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Result: Corrosive

Remarks: May cause severe irritation with corneal injury which may result in permanent

Issue Date: 11/02/2017 Liquid Hardener for PRF Wood Adhesives

impairment of vision, even blindness. Chemical burns may occur. Mist may cause eye irritation.

Result: Corrosive

Remarks: May cause severe irritation with corneal injury which may result in permanent

impairment of vision, even blindness. Chemical burns may occur.

Mist may cause eye irritation.

# Respiratory or skin sensitization

#### **Product:**

Assessment: Skin sensitiser Remarks: For skin sensitization:

Has caused allergic skin reactions when tested in guinea pigs.

Results from human studies indicate that this material has the potential to cause an allergic skin

reaction at high concentrations.

Remarks: For respiratory sensitization:

No relevant data found.

# Components:

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Assessment: May cause sensitisation by skin contact.

Remarks: Has caused allergic skin reactions when tested in guinea pigs.

Results from human studies indicate that this material has the potential to cause an allergic skin

reaction at high concentrations.

Remarks: For respiratory sensitization:

No relevant data found.

Assessment: May cause sensitisation by skin contact.

Remarks: Has caused allergic skin reactions when tested in guinea pigs.

Results from human studies indicate that this material has the potential to cause an allergic skin reaction at high concentrations.

Remarks: For respiratory sensitization:

No relevant data found.

## Carcinogenicity

#### Product:

No relevant data found.

# Components:

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

No relevant data found.

No relevant data found.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

Issue Date: 11/02/2017

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **Teratogenicity**

#### Product

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

#### **Components:**

## 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

## Mutagenicity

#### **Product**

Animal genetic toxicity studies were negative.

In vitro genetic toxicity studies were predominantly negative.

#### Components:

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Animal genetic toxicity studies were negative.

In vitro genetic toxicity studies were predominantly negative.

Animal genetic toxicity studies were negative.

In vitro genetic toxicity studies were predominantly negative.

## Reproductive toxicity

#### **Product:**

In animal studies, did not interfere with reproduction.

#### Components:

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

In animal studies, did not interfere with reproduction.

In animal studies, did not interfere with reproduction.

# STOT - single exposure

# **Product:**

Assessment: Available data are inadequate to determine single exposure specific target organ toxicity.

Issue Date: 11/02/2017

#### **Components:**

## 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Assessment: Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Assessment: Evaluation of available data suggests that this material is not an STOT-SE toxicant.

## Repeated dose toxicity

#### **Product:**

Remarks: In animals, effects have been reported on the following organs after ingestion: Stomach.

#### Components:

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Remarks: In animals, effects have been reported on the following organs: Stomach.

Remarks: In animals, effects have been reported on the following organs: Stomach.

# **Aspiration toxicity**

# **Product:**

Aspiration Hazard Based on physical properties, not likely to be an aspiration hazard.

# **Components:**

#### 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Based on physical properties, not likely to be an aspiration hazard.

Based on physical properties, not likely to be an aspiration hazard.

#### 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

#### **Product:**

Toxicity to fish

Remarks: Material is moderately toxic to fish on an acute

Issue Date: 11/02/2017

basis (LC50 between 1 and 10 mg/L).

LC50 (Oncorhynchus mykiss (rainbow trout)): 244 mg/l

Exposure time: 96.0 h Test Type: flow-through test

Method: OECD Test Guideline 203 or Equivalent

LC50 (Lepomis macrochirus (Bluegill sunfish)): 130 mg/l

Exposure time: 96.0 h Test Type: static test

Toxicity to daphnia and other aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 16.90 mg/l

Exposure time: 48.0 h Test Type: flow-through test

Method: OECD Test Guideline 202 or Equivalent

GLP: yes

EC50 (eastern oyster (Crassostrea virginica)): 35.00 mg/l

Exposure time: 96.0 h Test Type: flow-through test

LC50 (pink shrimp (Penaeus duorarum)): 138.00 mg/l

Exposure time: 96.0 h Test Type: static test

Toxicity to algae ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.08

mg/l

End point: Growth rate inhibition

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201 or Equivalent

ErC50 (Skeletonema costatum): 2.09 mg/l

End point: Growth rate inhibition

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201 or Equivalent

NOEC (Scenedesmus capricornutum (fresh water algae)):

0.513 mg/l

End point: Growth rate Exposure time: 72 h Test Type: semi-static test

Method: OECD Test Guideline 201 or Equivalent

Toxicity to bacteria EC50 (activated sludge): 166 mg/l

End point: Respiration rates.

14 / 24

Issue Date: 11/02/2017 Liquid Hardener for PRF Wood Adhesives

> Exposure time: 3 h Method: OECD 209 Test

# Components:

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Toxicity to fish Remarks: Material is moderately toxic to aquatic organisms on

an acute basis (LC50/EC50 between 1 and 10 mg/L in the

most sensitive species tested).

LC50 (Oncorhynchus mykiss (rainbow trout)): 244 mg/l

Exposure time: 96.0 h Test Type: flow-through test

Method: OECD Test Guideline 203 or Equivalent

LC50 (Lepomis macrochirus (Bluegill sunfish)): 130 mg/l

Exposure time: 96.0 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 16.90 mg/l

Exposure time: 48.0 h Test Type: flow-through test

Method: OECD Test Guideline 202 or Equivalent

EC50 (eastern oyster (Crassostrea virginica)): 35.00 mg/l

Exposure time: 96.0 h Test Type: flow-through test

LC50 (pink shrimp (Penaeus duorarum)): 138.00 mg/l

Exposure time: 96.0 h Test Type: static test

Toxicity to algae ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.08

ma/l

End point: Growth rate inhibition

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201 or Equivalent

ErC50 (Skeletonema costatum): 2.09 mg/l

End point: Growth rate inhibition

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201 or Equivalent

Toxicity to bacteria EC50 (activated sludge): 166 mg/l

End point: Respiration rates.

Exposure time: 3 h Method: OECD 209 Test

Toxicity to terrestrial

organisms

dietary LC50 (Colinus virginianus (Bobwhite quail)): > 5,000

Exposure time: 8 d

dietary LC50 (Anas platyrhynchos (Mallard duck)): > 5,000

Exposure time: 8 d

Issue Date: 11/02/2017 Liquid Hardener for PRF Wood Adhesives

oral LD50 (Colinus virginianus (Bobwhite quail)): 1,100 mg/kg

Exposure time: 1 d

Method: Method Not Specified.

**Ecotoxicology Assessment** 

Chronic aquatic toxicity Harmful to aquatic life with long lasting effects.

4-Ethyl-4-(hydroxymethyl)oxazolidine

Remarks: No relevant data found. Toxicity to fish

Toxicity to fish Remarks: Material is moderately toxic to aquatic organisms on

an acute basis (LC50/EC50 between 1 and 10 mg/L in the

most sensitive species tested).

LC50 (Oncorhynchus mykiss (rainbow trout)): 244 mg/l

Exposure time: 96.0 h Test Type: flow-through test

Method: OECD Test Guideline 203 or Equivalent

LC50 (Lepomis macrochirus (Bluegill sunfish)): 130 mg/l

Exposure time: 96.0 h Test Type: static test

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 16.90 mg/l

Exposure time: 48.0 h Test Type: flow-through test

Method: OECD Test Guideline 202 or Equivalent

EC50 (eastern oyster (Crassostrea virginica)): 35.00 mg/l

Exposure time: 96.0 h Test Type: flow-through test

LC50 (pink shrimp (Penaeus duorarum)): 138.00 mg/l

Exposure time: 96.0 h Test Type: static test

ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.08 Toxicity to algae

mg/l

End point: Growth rate inhibition

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201 or Equivalent

ErC50 (Skeletonema costatum): 2.09 mg/l

End point: Growth rate inhibition

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201 or Equivalent

EC50 (activated sludge): 166 mg/l Toxicity to bacteria

End point: Respiration rates.

Exposure time: 3 h Method: OECD 209 Test

Issue Date: 11/02/2017 Liquid Hardener for PRF Wood Adhesives

Toxicity to terrestrial

organisms

dietary LC50 (Colinus virginianus (Bobwhite quail)): > 5,000

Exposure time: 8 d

dietary LC50 (Anas platyrhynchos (Mallard duck)): > 5,000

ppm

Exposure time: 8 d

oral LD50 (Colinus virginianus (Bobwhite quail)): 1,100 mg/kg

Exposure time: 1 d

Method: Method Not Specified.

**Ecotoxicology Assessment** 

Chronic aquatic toxicity

Harmful to aquatic life with long lasting effects.

## Persistence and degradability

# **Product:**

Biodegradability

Remarks: This material rapidly hydrolyzes to products that are

either readily or ultimately biodegradable.

Abiotic degradation: The material is rapidly degradable by

abiotic means.

Biodegradation: 14 % Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

Remarks: 10-day Window: Not applicable

Biodegradation: 27 % Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Remarks: 10-day Window: Fail

Biodegradation: 19.1 % Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Remarks: 10-day Window: Fail

ThOD 2.350 mg/mg

Method: Estimated.

Stability in water Test Type: Hydrolysis

Degradation half life (DT50): 0.089 - 9.6 h (15 °C) pH: 4 - 9

Method: OECD Test Guideline 111 Remarks: Hydrolyses readily.

Test Type: Hydrolysis

Degradation half life (DT50): 0.1 - 3.799 h (25 °C) pH: 4 - 9

Method: OECD Test Guideline 111 Remarks: Hydrolyses readily.

Photodegradation Rate constant: Degradation half life: 1.5 d

Method: Estimated.

Product name : ZOLDINE™ LH 2001, Rapid Cure Issue Date: 11/02/2017 Liquid Hardener for PRF Wood Adhesives

#### **Components:**

#### 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Biodegradability Result: Readily biodegradable

Remarks: This material rapidly hydrolyzes to products that are

either readily or ultimately biodegradable.

Abiotic degradation: The material is rapidly degradable by

abiotic means.

Biodegradation: 14 % Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

Remarks: 10-day Window: Not applicable

Biodegradation: 19.1 % Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Remarks: 10-day Window: Fail

Biodegradation: 27 % Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Remarks: 10-day Window: Fail

ThOD 2.350 mg/mg

Stability in water Test Type: Hydrolysis

Degradation half life (DT50): 0.089 - 9.6 h (15 °C) pH: 4 - 9

Method: OECD Test Guideline 111 Remarks: Hydrolyses readily.

Test Type: Hydrolysis

Degradation half life (DT50): 0.1 - 3.799 h (25 °C) pH: 4 - 9

Method: OECD Test Guideline 111 Remarks: Hydrolyses readily.

Photodegradation Rate constant: Degradation half life: 0.0625 h

Method: Estimated.

# 4-Ethyl-4-(hydroxymethyl)oxazolidine

Biodegradability Remarks: No relevant data found.

Biodegradability Result: Readily biodegradable

Remarks: This material rapidly hydrolyzes to products that are

either readily or ultimately biodegradable.

Abiotic degradation: The material is rapidly degradable by

abiotic means.

Biodegradation: 14 % Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

Remarks: 10-day Window: Not applicable

Biodegradation: 19.1 %

Issue Date: 11/02/2017 Liquid Hardener for PRF Wood Adhesives

Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Remarks: 10-day Window: Fail

Biodegradation: 27 % Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Remarks: 10-day Window: Fail

ThOD 2.350 mg/mg

Stability in water Test Type: Hydrolysis

Degradation half life (DT50): 0.089 - 9.6 h (15 °C) pH: 4 - 9

Method: OECD Test Guideline 111 Remarks: Hydrolyses readily.

Test Type: Hydrolysis

Degradation half life (DT50): 0.1 - 3.799 h (25 °C) pH: 4 - 9

Method: OECD Test Guideline 111 Remarks: Hydrolyses readily.

Photodegradation Rate constant: Degradation half life: 0.0625 h

Method: Estimated.

## Bioaccumulative potential

**Product:** 

Bioaccumulation Species: Fish.

Bioconcentration factor (BCF): 2 - 3

Method: Measured

Partition coefficient: n-

octanol/water

log Pow: -0.32

Method: EC Method A6

Remarks: Bioconcentration potential is low (BCF < 100 or Log

Pow < 3).

#### Components:

#### 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Bioaccumulation Species: Fish.

Bioconcentration factor (BCF): 2 - 3

Method: Measured

Partition coefficient: n-

octanol/water

log Pow: -0.32 (25 °C) Method: EC Method A6

Remarks: Bioconcentration potential is low (BCF < 100 or Log

Pow < 3).

Bioaccumulation Species: Fish.

Bioconcentration factor (BCF): 2 - 3

Method: Measured

Partition coefficient: n-

octanol/water

log Pow: -0.32 (25 °C) Method: EC Method A6

Liquid Hardener for PRF Wood Adhesives

Remarks: Bioconcentration potential is low (BCF < 100 or Log

Issue Date: 11/02/2017

Pow < 3).

# Mobility in soil

#### **Product:**

Distribution among Koc: 10

environmental compartments Method: Estimated.

Remarks: Potential for mobility in soil is very high (Koc

between 0 and 50).

## **Components:**

## 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Distribution among Koc: 10

environmental compartments Method: Estimated.

Remarks: Potential for mobility in soil is very high (Koc

between 0 and 50).

# 4-Ethyl-4-(hydroxymethyl)oxazolidine

Distribution among

environmental compartments

Remarks: No relevant data found.

Distribution among Koc: 10

environmental compartments Method: Estimated.

Remarks: Potential for mobility in soil is very high (Koc

between 0 and 50).

#### Other adverse effects

#### **Product:**

Ozone-Depletion Potential Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

# **Components:**

# 7a-Ethyldihydro-1H,3H,5H-oxazolo(3,4-c)oxazole

Results of PBT and vPvB

assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating

(vPvB).

Ozone-Depletion Potential Remarks: No relevant data found.

Liquid Hardener for PRF Wood Adhesives

#### 4-Ethyl-4-(hydroxymethyl)oxazolidine

Results of PBT and vPvB

assessment

This substance has not been assessed for persistence,

Issue Date: 11/02/2017

bioaccumulation and toxicity (PBT).

Results of PBT and vPvB

assessment

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating

(vPvB).

Ozone-Depletion Potential Remarks: No relevant data found.

#### 13. DISPOSAL CONSIDERATIONS

## **Disposal methods**

Waste from residues

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND,

OR INTO ANY BODY OF WATER.

All disposal practices must be in compliance with all Federal,

State/Provincial and local laws and regulations. Regulations may vary in different locations.

Waste characterizations and compliance with applicable laws

are the responsibility solely of the waste generator.

AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS

MATERIAL.

THE INFORMATION PRESENTED HERE PERTAINS ONLY

TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION:

Composition Information.

FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted:

Incinerator or other thermal destruction device.

Landfill.

#### 14. TRANSPORT INFORMATION

## International Regulation

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**National Regulations** 

49 CFR (DOT) - NON BULK

Not regulated as a dangerous good

#### 49 CFR (DOT) - BULK

UN/ID/NA number NA 1993

Proper shipping name COMBUSTIBLE LIQUID, N.O.S.

(7a-Ethyldihydro-1H,3H,5H-oxazolo[3,4-c]oxazole)

Issue Date: 11/02/2017

Class CBL
Packing group III
ERG Code 128
Marine pollutant no

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

#### 15. REGULATORY INFORMATION

OSHA Hazards This product is a "Hazardous Chemical" as defined by the

OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

SARA 311/312 Hazards Fire Hazard

Acute Health Hazard

SARA 302 No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

## **US State Regulations**

# **Massachusetts Right To Know**

No components are subject to the Massachusetts Right to Know Act.

# **New Jersey Right To Know**

The following chemicals are listed because of the additional requirements of New Jersey law:

Cas No. Component 53019-53-7 4-Ethyl-1,3-oxazolidine

## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Issue Date: 11/02/2017


# The components of this product are reported in the following inventories:

United States TSCA Inventory All Components OK

#### 16. OTHER INFORMATION

# **Further information**

# NFPA:



# HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

**Revision Date** 11/02/2017 Version 0.0

Identification Number: 000040000149

#### US / EN

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue Date: 11/02/2017

#### Full text of other abbreviations

(Q)SAR - (Quantitative) Structure Activity Relationship; ASTM - American Society for the Testing of Materials; bw - Body weight; DIN - Standard of the German Institute for Standardisation; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative; DSL - Domestic Substances List (Canada); KECI - Korea Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); AICS - Australian Inventory of Chemical Substances; IECSC - Inventory of Existing Chemical Substances in China; ENCS - Existing and New Chemical Substances (Japan); ISHL - Industrial Safety and Health Law (Japan); PICCS - Philippines Inventory of Chemicals and Chemical Substances; NZIoC -New Zealand Inventory of Chemicals; TCSI - Taiwan Chemical Substance Inventory; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; DOT - Department of Transportation; EHS - Extremely Hazardous Substance; HMIS - Hazardous Materials Identification System; MSHA - Mine Safety and Health Administration; NFPA - National Fire Protection Association; RCRA - Resource Conservation and Recovery Act; RQ - Reportable Quantity; SARA - Superfund Amendments and Reauthorization Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; GLP -Good Laboratory Practice; ERG - Emergency Response Guide; NTP - National Toxicology Program; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods